NEW!

C-CASSETTE
Round way cassette indoor units

Colour
White matt (cover)

Temperature setpoint from 16 to 30°C



The HEIKO C-CASSETTE Round way cassette unit, also available in the MULTI SPLIT system, is a new addition to the offer intended for offices, commercial premises and other commercial spaces. The 360° airflow and SMART Airflow function ensure even and comfortable air distribution in multiple rooms at the same time, while quiet operation, TURBO and SLEEP modes and a visually attractive panel combine effective climate control with an elegant design.

- High energy efficiency
- SMART airflow
- 5 operating modes
- Inverter technology
- Automatic defrosting
- DC motor
- Hydrophilic aluminium foil
- Silent operation
- Round way airflow

Indoor unit



Cover (optional)
PB-950H-A2R



Wireless controller (option)
YR-NRS01



Wired controller (option)
YR-C01



C-CASSETTE CASSETTE INDOOR UNITS | ROUND						
INDOOR UNIT					**CA070-A2R**	**CA100-A2R**
OUTDOOR UNIT					**JZ070-A2**	**JZ100-A2**
Rated value	Performance	Cooling	Btu/h (rated)		24200	32400
			Rated kW (min - max)		7.1 (2.0-8.2)	9.5 (2.5-10.0)
		Heating	Btu/h (rated)		27000	35800
			Rated kW (min - max)		7.9 (2.5-8.5)	10.5 (3.0-12.5)
	Energy Consumption	Cooling	Rated kW (min - max)		2.2 (0.5-4.0)	2.79 (0.5-4.0)
		Heating	Rated kW (min - max)		2.13 (0.5-4.0)	2.83 (0.5-4.0)
	EER/COP				3.23/3.72	3.4/3.71
Seasonal value	SEER/SCOP				6.1/4.0	6.2/4.05
	Energy rating (cooling/heating)				A++/A+	A++/A+
	Annual energy consumption (cooling)			kWh	406	544
	Annual energy consumption (heating)			kWh	1831	2792
INDOOR UNIT					**CA070-A2R**	**CA100-A2R**
Electrical rating	Power supply			Ph/V/Hz	1/220-240/50/60	1/220-240/50/60
Performance	Airflow			m^3/h	1260/1100/900/700	1920/1750/1550/1250
	Sound Power Level			DB(A)	57	62
	Sound pressure level			DB(A)	42/40/38/35	45/42/38/34
Installation	Net dimensions (W/D/H)			mm	840/840/204	840/840/246
	Packaged dimensions (W/D/H)			mm	978/978/269	978/978/269
	Weight, net/gross			kg	23/28	24/31
	Control unit			wireless option	YR-NRS01	YR-NRS01
				wired option	YR-C01	YR-C01
Cover	Model			option	PB-950H-A2R	PB-950H-A2R
	Dimensions (W/D/H)			mm	950/950/50	950/950/50
	Packaged dimensions (W/D/H)			mm	1013/1035/125	1013/1035/125
	Weight, net/gross			kg	5.5/8.5	5.5/8.5
OUTDOOR UNIT					**JZ070-A2**	**JZ100-A2**
Electrical rating	Power supply			Ph/V/Hz	1/220-240/50/60	1/220-240/50/60
Performance	Airflow (h)			m^3/h	3000	3500
	Sound Power Level			DB(A)	68	68
	Sound pressure level			DB(A)	54	54
Installation	Net dimensions (W/D/H)			mm	890/340/700	950/370/815
	Packaged dimensions (W/D/H)			mm	985/430/720	1085/465/850
	Weight, net/gross			kg	37/42	56/60
	Compressor type				Twin, rotary	Twin, rotary
	Refrigerant				R32	R32
	GWP				675	675
	Liquid pipe diameter			mm	9.52	9.52
	Gas pipe diameter			mm	15.88	15.88
	Total piping length (max)			m	50	50
	Max level difference			m	30	30
	Refrigerant charge			kg	1.3	1.7
	Total piping length without extra charge			m	10	30
	Extra refrigerant charge per metre of piping			g/m	45	45
Operating conditions (out)	Cooling (min - max)			°C	-20 ~ 46	-20 ~ 46
	Heating (min - max)			°C	-20 ~ 24	-20 ~ 24

CA070-A2R



CA100-A2R



JZ070-A2



JZ100-A2

